

The notes shown below are an exact transcript of the original field notes for the establishment of the east line of Section 1, T2N, R4E of the Black Hills Meridian including the establishment of the township corner at the NE Corner of Section 1, T2N, R4E. These notes are contained in the Instructions to U. S. Surveyors A. L. Coleman and F. M. Johnson dated July 23, 1897, and are on file at the Montana State Office of the Bureau of Land Management in Billings, Montana.

East boundary of T. 2 N., R. 4 E.

Chains North bet. secs. 1 and 6.  
Over rolling land, through heavy timber.

28.00 Ravine, course S. 40° E. Ascend.

40.00 Set a quartz stone, 16x11x3 ins., 10 ins. in the ground, for 1/4 sec. cor., marked 1/4 on W. face; from which

A pine, 10 ins. diam., bears N 60°30' E., 13 lks. dist., marked 1/4 S., S. 6, B. T.

A pine, 12 ins. diam., bears N. 73° W., 24 lks. dist., marked 1/4 S., S. 1, B. T.

79.00 Summit of round top hill; descend.

80.00 Set a U. S. G. S. Iron post, 4 ft. long, 3 ft. in the ground, for cor. of Tps. 2 and 3 N., Rs. 4 and 5 E., marked

T. 3 N., S. 31, on N. E. quadrant,

R. 5 E., S. 6, on S. E. "

T. 2 N., S. 1, on S. W. "

R. 4 E., S. 36, on N. W. "

with 6 notches on N., S., E., and W. edges of copper plate; from which

A pine, 10 ins. diam., bears N. 52° E., 160 lks. dist., marked T. 3 N., R. 5 E., S. 31, B. T.

A pine, 14 ins. diam., bears S. 43° E., 75 lks. dist., marked T. 2 N., R. 5 E., S. 6, B. T.

A pine, 22 ins. diam., bears S. 07° W., 29 lks. dist., marked T. 2 N., R. 4 E., S. 1, B. T.

A pine, 8 ins. diam., bears N. 72° W., 81 lks. dist., marked T. 3 N., R. 4 E., S. 36, B. T.

Land, rolling.  
Soil, stony; 3rd rate.  
Heavy pine timber, 80.00 chs.

November 13, 1897.

Original Monument

